



TEXTILE PRINTING

TEXILAC AIRTEX

Code N 167700

Technical Data Sheet N 58/TP

7th June 2002

Texilac Airtex is water based self-curing ink for printing on light fabrics.

No heating treatment is required.
Soft hand touch.
Excellent printability.
Wet-on-wet printing allowed.
Available in 14 colours including process colours.
Formaldehyde & lead-free.

- PREPARATION:** the colours are ready to use.
To reduce viscosity add water up to max. of 3%
To increase viscosity use TEXILAC ADDENSANTE 162 [Thickner] up to 0,5% max.
To slow down ink drying in the screen use TEXILAC RITARDANTE [Retarder] up to 3% max.
- PRINTING:** use screens with max 100 Th./cm.
- POLYMERIZATION:** TEXILAC AIRTEX achieves resistance to domestic washing after 4 days at room temperature. It is possible to speed up polymerization in hot air dryer at [120 140] C.
It is also possible to increase general fastness with the addition of ECOTEX FIX 50 up to 1%. The catalyzed ink can be used within 8-12 hours according to room conditions.
- CLEANING:** tools and screens have to be washed with cold water, immediately.
For a deep cleaning of the screen after long printing runs, use SCREEN CLEAN ST to be applied with a brush or a sponge.
- WARNING:** **Not compatible with OLD series 40N000 NEW AIRTEX [Argon]**
- PACKING:** 1 and 5 Kg for Transparent base, white and black.
1 Kg for colours.

ADVICE

The printing results depend on many factors and we recommended to make thorough preliminary tests to confirm our directions for use.
Mix thoroughly before use, Protect against freezing. All LECHLER spa products bear the safety labels complying with the current regulations and up-dated safety data sheets according to EEC norms are available upon request. VP n 956570.E n 05.97
IMPORTANT n Only the correct use of the product will allow satisfactory results. For this reason, closely related to the product supplied, Messrs. LECHLER must decline all direct and indirect responsibility for the proper or improper use of the product. Basic conditions for the right use and application of the product: make certain that products is right for the destined use - work according to the instructions given in our technical data sheets - before use contact our Technical Service in case of doubt. Messrs. LECHLER decline all direct or indirect responsibility for the sale of the product, in case the buyer, in use and application of the product, has omitted to proceed according to the above mentioned condition. In relation to the many methods and application possibilities of the product, the seller declines responsibility in case application or use of the product should prejudice rights of a third party.

LECHLER SPA n V.A. De Gasperi, 1 n 22070 LUISAGO (Co)

Distributör Sverige:
Svenska Handtryck AB, Sockenvägen 536, 121 34 Enskededalen
Tel 08-659 06 06 Mail info@svenska-handtryck.se