

TEXILAC APS TRASPARENTE

Code No 168750

Technical Data Sheet N 15/TP

11th April 2009

Transparent water-based textile printing binder.

water-based product for direct printing on a large range of materials
for soft prints on light-coloured fabrics
polymerization at room temperature after catalyzation
the prints resist washing with water at 40°C
can be used for four-colour-process and wet-on wet printing

- PREPARATION** : TEXILAC APS TRASPARENTE is ready for use and can be diluted with max 5% of water.
For polymerization at room temperature, the product is to be catalyzed with 0,3% of catalyst CATALIZZATORE APS N.
Pot-life: 12 hours. Environmental conditions may influence the durability of the mixture and reduce its pot-life. Prepare only the quantity needed for daily use.
Drying can be slowed by adding max 1-3% TEXILAC RITARDANTE GEL (Texilac Gel Retarder).
If necessary, the product can be thickened with max 0.5-1% TEXILAC ADDENSANTE 346 (thickener).
To print coarser fabrics, dilution up to 5% water is possible.
- COLOURS** : use max 3% of TEXILAC COLORANTI (colorants) or ECOTEX P pigments (white, black and blue royal OL = max 5%).
The pigments for four-colour-process printing are indicated in the shade card TEXILAC COLORANTI
- PRINTING** : flat screens: max 120 th/cm.
- CLEANING** : screens and tools can be washed with cold water, immediately after the use
- POLYMERIZATION** : when used with catalyst, the prints are dry and resistant to washing with water after approx. 48 hours at room temperature.
Without catalyst, heat cure the prints for three minutes at 140°C.
- PACKINGS** : TEXILAC APS TRASPARENTE 1, 5, 20 and 50 kg.
CATALIZZATORE APS N (177363) 0.1 and 1 kg.

TEXILAC APS TRASPARENTE has not to be mixed with other products.

ADVICE

The printing results depend on many factors and we recommend to make thorough preliminary tests to confirm our directions for use.
Mix thoroughly before use, Protect against freezing. All LECHLER spa products bear the safety labels complying with the current regulations and up-dated safety data sheets according to EEC norms are available upon request.

IMPORTANT Only the correct use of the product will allow satisfactory results. For this reason, closely related to the product supplied, Messrs. LECHLER must decline all direct and indirect responsibility for the proper or improper use of the product. Basic conditions for the right use and application of the product: make certain that products is right for the destined use - work according to the instructions given in our technical data sheets - before use contact our Technical Service in case of doubt. Messrs. LECHLER decline all direct or indirect responsibility for the sale of the product, in case the buyer, in use and application of the product, has omitted to proceed according to the above mentioned condition. In relation to the many methods and application possibilities of the product, the seller declines responsibility in case application or use of the product should prejudice rights of a third party.

LECHLER SPA s.p.a. De Gasperi, 1 22070 LUISAGO (Co)

Distributör Sverige:

Svenska Handtryck AB

Sockenvägen 536, 121 34 Enskededalen. Tel: 08-659 06 06 Internet: www.screenorama.com